Adapter frames



Features

- · Suitable for Han-Modular® modules
- · Fast and tool-less assembly
- · Snap-in assembly from mating side and from termination side
- · Removal from mating side and from termination side possible

Technical characteristics

Flammability (insert) acc. to V 0

UL 94

Material (insert) PC

Colour (insert) RAL 7032 (light grey)

Specifications and approvals

IEC 60664-1 IEC 61984



Details

Han-Yellock® adapter frame

Han-Modular® series interfaces can be established using the Han-Yellock® adapter frame. The connection is based on a male/female contact arrangement.

Inserting the adapter frame in the housing:

The adapter frame can be snapped into the housing, bulkhead mounting, on the termination side and the mating side (refer to the illustration).

The lateral plastic tabs ("B") are pressed into the metal clamps on the housing.

The adapter frame then snaps in with a distinctly audible click.

① metal clamp

Removal of the adapter frame:


The removal tool part no. 11 99 000 0001 is required for disassembly. (see chapter 90)

The removal tool is inserted into the metal clamp and pressed down as shown in the following illustration. A screwdriver need also be placed into the notch in the housing.

The removal tool should then be pulled outwards to remove the adapter frame from the housing.

The removal can be made from the termination side as well as from the mating side.

The process is identical for both housings, bulkhead mounting, and carrier hoods.



Yellock

Adapter frames



Identification		Part number	Drawing Dimensions in mm	
Han-Yellock®, Adapter frames, for Han-Yellock® 30 +60, for housings bulkhead mounting		11 00 200 0301	1 10 20 00 00 10 10 10 10 10 10 10 10 10 10 10	19,5
Mounting/removal from termination s Han- Yellock*, Adapter frames, for Han- Yellock* 30, for housings bulkhead mounting	ide only!	11 00 300 0301	40	11 20 30 (35) 30 30 (35) 34 , 85
Han- Yellock*, Adapter frames, for Han- Yellock* 60, for housings bulkhead mounting		11 00 600 0301	1 % at 1	64,25
Han-Yellock*, Adapter frames, for Han-Yellock* 30 +60, for carrier hoods		11 00 200 0101	11 to 130 et	19,5
Mounting/removal from termination s Han- Yellock*, Adapter frames, for Han- Yellock* 30, for carrier hoods	ide only!	11 00 300 0101	40,1	34,85 —

Han-Yellock

Adapter frames




Identification


Han-Yellock®, Adapter frames, for Han-Yellock® 60, for carrier hoods



11 00 600 0101

Drawing Dimensions in mm





Combinations	Han-Yellock® Hood/Housing					
	30	30	60	60	60	
Han-Yellock® 20 Adapter frame (for Han-Yellock® 30 und 60)	Y		2	1		
Han-Yellock® 30 Adapter frame		1				
Han-Yellock® 60 Adapter frame			-		1	
Han-Yellock® Module	1		2	4		

Han-Yellock